

CUSTOMpine Whiteboard

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name	Borg Manufacturing, ABN 31 003 246 357
Address	2 Wella Way, Somersby, NSW, Australia, 2250
Telephone	1300 500 250 / 02 4340 9800
Facsimile	1300 500 255 / 02 4340 5841
Emergency	1300 300 547
Synonyms	CUSTOMpine CUSTOMpine Whiteboard CUSTOMpine Shelving
Use	Building board, cabinets, door facings, furniture

2. HAZARD IDENTIFICATION

Not classified as hazardous according to ASCC Criteria. Not classified as a hazardous substance by the criteria of the ADG Code.

UN Number	None Allocated
Hazchem Code	None Allocated
Packing Group	None Allocated
Poisons Schedule Number	None Allocated

3. COMPOSITION/INFORMATION OF INGREDIENTS

Ingredient	Formula	CAS No.	Content
Paraffin Wax	Not Available	8002-74-2	<1%
Softwood(s)	Not Available	None	>80%
Urea formaldehyde (UF) resin or	Not Available	9011-05-6	<20%
Melamine urea formaldehyde (MUF) resin	Not Available	25036-13-9	<20%
Decorative Paper	Not Available	None	<2%

Notes: Melamine urea formaldehyde resin is used in MR boards and urea formaldehyde resin is also used in STD board. The above ingredients are bound together under heat and pressure. The process cures the resin, but small amount of formaldehyde from the resin may be released from the finished product. Formaldehyde content in the finished product complies with the Australian Standard (AS/NZS 1859) E1 requirement when tested to AS/NZS 4266.16 (Desiccator test).

4. FIRST AID MEASURES

Ingestion	Give water to drink. If abdominal discomfort continues, contact a Poisons Information Centre on 13 11 26 (Australia wide) or a doctor (at once). Due to product form and application, ingestion is considered unlikely.
Eye	If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
Skin	Wash with mild soap and running water. Remove clothing contaminated with wood dust.
Inhalation	If inhaled, remove from the contaminated area.
Advice to Doctor	Treat symptomatically.

5. FIRE FIGHTING MEASURES

Fire and Explosion	Burning or smouldering boards or dust can generate carbon dioxide and other pyrolysis products typical of burning organic material which are irritating to the respiratory tract. Dry dusts in high concentrations can be explosive. Use water, CO ₂ , foam or dry chemical fire extinguishers and avoid breathing smoke from burning or smouldering material.
--------------------	---

CUSTOMpine Whiteboard

6. ACCIDENTAL RELEASE MEASURES

Spillage and Disposal	Off-cuts, general waste material and protective plastic film should be placed in containers and disposed of at approved landfill sites, or burnt in an approved furnace or incinerator, in accordance with disposal authority guidelines. DO NOT BURN in barbeques, combustion stoves or any open fires in home as irritating gases are emitted. Dust from the boards should be cleaned up by vacuuming or wet sweeping.
-----------------------	---

7. STORAGE AND HANDLING

Storage	The panels should be stored in well-ventilated areas away from sources of heat, flame or sparks. No special transport requirements are considered necessary.
Handling	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking or smoking in contaminated areas.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Standard	The Worksafe Australia Exposure Standards, published in May 1995 are: Wood dust (softwood) 5mg/cubic metre time-weighted average (TWA) measured as inspirable particulates. 10mg/cubic metre short term exposure limit (STEL). It is also listed as a sensitiser. Formaldehyde 1.0ppm (1.2mg/cubic metre) time-weighted average (TWA) 8 hours. 2.0ppm (2.5mg/cubic metre) short term exposure limit 15 minutes (STEL). It is also listed as a sensitiser. Category 2 carcinogen (probable human carcinogen). Paraffin wax (fume) 2mg/cubic metre time-weighted average (TWA) 8 hours. Keep exposures as low as practicable with the aim of maintaining inspirable wood dust levels below 1.0mg/cubic metre (TWA).
Engineering Controls	All work with these boards should be carried out in such a way as to minimise the generation of, and exposure to dust. Under factory conditions, sawing, drilling, sanding etc. should be done with equipment fitted with exhaust devices capable of removing wood dust, at source. Hand power tools should be fitted with dust bags and used in well-ventilated areas. Work areas should be well-ventilated. They should be cleaned at least daily, and dust removed by vacuum cleaning or wet sweeping method. It is recommended that all work and storage areas are smoke free and other airborne contaminants be kept to a minimum.
Skin Protection	Wear loose, comfortable clothing. Long-sleeved shirts and trousers are recommended to prevent skin irritation. After handling boards, wash with mild soap and water. Do not scratch or rub the skin if it becomes irritated. Wash work clothes regularly and separately from other clothes. Comfortable lightweight leather or equivalent work gloves (AS 2161) should be worn.
Eye Protection	Dust resistant safety glasses or non-fogging goggles (AS/NZS 1336/1337) should be worn when machining.
Respiratory Protection	A class P1 or P2 replaceable filter or disposable half face-piece particulates respirator should be worn when machining. Respirators should comply with AS/NZS 1716 and be selected, used and maintained in accordance with AS/NZS 1715.
Flammability	These boards are flammable but difficult to ignite. Fine airborne dust can ignite so avoid a build-up of dust and keep all storage and work areas well ventilated. Avoid sources of radiant heat and flame; and avoid sparks and sources of ignition in all electrical equipment, including dust extraction equipment. People must not smoke in storage or work areas.

CUSTOMpine Whiteboard

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	The boards are manufactured as pressed boards ranging in thickness from 9mm to 33mm. They are made from plantation wood fibres or flakes, which are bonded together with resin (glue). The product is surfaced with a decorative paper impregnated with resin. Only Moisture Resistance (MR) particle-boards have a blue-green core.		
Odour	Newly manufactured and freshly cut surfaces may have a paint pine and resin odour.		
Boiling Point (°C)	Not Applicable	Flammability Limits	Not Applicable
Vapour Pressure	Not Applicable	Early Fire Hazard Indices to	AS 1530.3
Flashpoint	Not Applicable	Ignitability Index	12 - 14
Solubility in Water	Negligible	Spread of flame index	5 - 7
Melting Point (°C)	Not Applicable	Heat Evolved Index	4 - 6
Specific Gravity (water=1)	0.6 - 0.8	Smoke Developed Index	3 - 5
Autoignition Temperature	Does not auto ignite in its intact state		

10. TOXICOLOGICAL INFORMATION

Health Hazard Information

Formaldehyde gas may be released under some conditions. However, in well-ventilated storage areas and workplaces, the concentration of formaldehyde is unlikely to exceed the World Health Organisation standard of 0.1ppm for the general environment and it will be well below the Worksafe Australia occupational Exposure Standard of 1.0 ppm. Wood dust will be given off from machining the product, and gas and vapour may be produced from heat processing. The known health effects from wood dust and formaldehyde are as follows:

Wood Dust Dust and splinters may cause irritation of the nose and throat, eyes and skin. Some woods may also be sensitisers, and some people may develop allergic dermatitis or asthma. Inhalation of wood dust may increase the risk of nasal and paranasal sinus cancer. Wood dust has been evaluated by the International Agency for Research on Cancer (IARC) as Group 1, carcinogenic to humans.

Formaldehyde Formaldehyde gas and dilute solution of formaldehyde in water are irritating to the nose and throat, eyes and skin. The solutions are also sensitisers and contact dermatitis has been reported.
Formaldehyde has been evaluated by the International Agency for Research on Cancer (IARC) as group 2A, probably carcinogenic to humans. The IARC again evaluated formaldehyde in June 2004 and concluded that: "There are adequate data available from humans for an increased risk of nasopharyngeal cancer" and that formaldehyde should now be classified as Group 1, carcinogenic to humans.

Worksafe Australia has listed Formaldehyde as Sensitiser and Category 2 carcinogen (probable human carcinogen) as "those substances for which there is sufficient evidence to provide a strong presumption that human exposure may result in the development of cancer. This evidence is generally based on appropriate long term animal studies, limited epidemiological evidence or other relevant information".

Exposures to wood dust produced from machining the products, and gas and vapour from heat processing with inadequate ventilation may result in the following health effects:

Ingestion	Unlikely to occur but swallowing the dust may result in abdominal discomfort.
Eye	The dust, gas and vapour may be irritating to the eyes causing discomfort and redness.
Skin	The dust, gas and vapour may irritate the skin, resulting in itching and occasionally a red rash.
Inhalation	The dust, gas and vapour may irritate the nose, throat and lungs, especially in people with upper respiratory tract or chest complaints such as asthma.
Chronic	Repeated exposure over many years to uncontrolled wood dust may increase the risk of nasal cavity cancer. Inhalation of wood dust may also increase the risk of lung fibrosis (scarring). There are also increased risks of respiratory and skin sensitisation from wood dust and formaldehyde, resulting in asthma and dermatitis respectively. But if the work practices noted in this SDS are followed and exposure to airborne dust are kept to a minimum, no chronic health effects are anticipated.

CUSTOMpine Whiteboard

11. ECOLOGICAL INFORMATION

Environment Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.

12. DISPOSAL CONSIDERATIONS

Waste Disposal Reuse where possible. Not regulated as a hazardous waste by Australian environmental authorities. Off-cuts and general waste material should be placed in containers and disposed of at approved landfill sites or burnt in an approved furnace or incinerator in accordance with disposal authority guidelines. Do not burn in barbecues, combustion stoves or open fires in the home as irritating gases may be evolved.

Legislation Dispose of in accordance with relevant local legislation.

13. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	None Allocated	DG Class	None Allocated	Subsidiary Risk(s)	None Allocated
UN No.	None Allocated	Hazchem Code	None Allocated	EPG	None Allocated
Packing Group	None Allocated				

14. REGULATORY INFORMATION

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

15. OTHER INFORMATION

Respirators In general, the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn, ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

Combustible - Explosive
Carbonaceous Dust Carbonaceous/organic dusts have the potential, with dispersion, to present an explosion hazard if an ignition source exists. All equipment used to handle, transfer or store this product MUST BE cleaned thoroughly prior to cutting, welding, drilling or exposure to any other form of heat or ignition sources. If bulk stored, containers should be ventilated on a routine basis to avoid vapour accumulation (where applicable, eg. for flocculants).

Health Effects from
Exposure It should be noted that the effects from exposure to this product would depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that, it is impractical to prepare a Chem Alert report, which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Personal Protective
Equipment Guidelines The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Health Effects from
Exposure It should be noted that the effects from exposure to this product would depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that, it is impractical to prepare a Chem Alert report, which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

CUSTOMpine Whiteboard

Personal Protective Equipment Guidelines	The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.
Abbreviations	<p>MDF - Medium Density Fibre Board</p> <p>LPM - Low Pressure Melamine</p> <p>CAS# - Chemical Abstract Service Number - Used to uniquely identify chemical compounds.</p> <p>CNS - Central Nervous System</p> <p>IARC - International Agency for Research on cancer</p> <p>M - moles per litre, a unit of concentration</p> <p>mg/m³ - Milligrams per cubic metre</p> <p>ppm - Parts Per Million</p> <p>TWA/ES - Time Weighted Average or Exposure Standard</p>

CONTACT

For further information on this product, contact:

Borg Manufacturing (ABN 31 003 246 357)

Address: 2 Wella Way Somersby NSW 2250 Australia **Telephone:** 1300 500 250 **Fax:** 1300 500 255

Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, we can accept no responsibility for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under condition beyond our control, we can accept no responsibility for any loss or damage caused by any person acting or refraining from action as a result of this information.

Date of last update: 11/7/19